

Recessed Light Enclosure for two-hour fire-rated ceiling

Architects, specifiers and installers can easily maintain the integrity of the fire-rated ceilings for two-hours by using the e.z. barrier enclosure and 3M Intumescent material. Both materials are fire-rated for one-hour each, combined for a two-hour enclosure.



**Recessed Light Enclosure
Intumescent lined,
Model #ezb 16-24-9I**

With the e.z. barrier two-hour fire-rated enclosure, recessed lights can be installed in a fraction of the time that it would take to hand build an enclosure. Once you fasten the four screws, your enclosure is ready to go. Simply install your light and you're on to the next one. You will reduce time and labor costs while ensuring compliance to building codes.

When it comes to two-hour fire-rated enclosures, count on e.z. barrier solutions from the fire-rated enclosure experts.

NOTE: Always check with the local inspector for final approval before ordering. Due to the lack of two-hour fire-rated enclosures on the market inspectors have approved our product as a solution especially in medical buildings.

We make it easy for you:

- Ez to install.**
- Ez to save money.**
- Ez to meet the fire code.**

Product Features for Model # ezb16-24-9I

- Fits both 16" and 24" on-center applications for walls or ceilings, Intumescent lined for add fire protection,
- Attaches quickly with drywall screws, saving time and labor, can be used on either interior or exterior applications,
- Features 4 knock-outs for wiring flexibility with access from any direction,
- Maintains air space when using blown-in insulation to eliminate overheating of fixtures,
- Keeps loose insulation out of eyes while installing speakers or LED flat downlights,
- Maintains vapor barrier integrity to meet new "tight building" codes,
- Can be used with either non-IC rated or IC rated fixtures,
- Maintenance free,
- Affixed directly to the structure,
- No product modifications required. Reduces risk of incorrect product installation or movement during or after construction,

Enclosure and Intumescent each meet One-Hour Fire-Rated Codes

Confines fire, gas, smoke and heat in the enclosure for 60 minutes, preventing leakage through the assembly into duct work.

Meets the following codes:

- **ASTM E-119-05a**
- **UL 263**
- **UBC 7-1**
- **NFPA 251**
- **ANSI A2.1**
- **ULC S101**



ISO Certified

SPECIFICATIONS

- **Flange: 2-5/8" wide for easy mounting,**
- **Material: Corrosion-resistant metal,**
- **Internal Dimensions: 19-7/8" long x 11-3/4" wide x 9" deep (included intumescent material).**